



ARROWHEAD DETAIL

SIGN SIZE	DIMENSIONS (Inches)												
	A	B	C	D	E	F	G	H	J	K	L	M	N
36 x 36	8-1/2	7-1/4	3/4	1-1/2	6	36	5/8	7/8	12D	8	2	12-1/2	2-1/4
48 x 48	11-5/16	9-5/8	1	2	8	48	3/4	1-1/4	16D	10-5/8	2-5/8	16-1/2	3
60 x 60	14-1/8	12	1-1/4	2-1/2	10	60	7/8	1-1/2	20D	13-1/4	3-1/4	20-5/8	3-3/4

COLORS
LEGEND & BORDER - BLACK (NON-REFLECTIVE)
BACKGROUND - YELLOW (REFLECTIVE)

- THE POLICY FOR INTENDED USAGE OF THIS SIGN IS SHOWN ON REVERSE SIDE -

Gerry Myers
 CHIEF, OFFICE OF SIGNS AND DELINEATION

4/4/00
 DATE

REVISION

REVISION

POLICY: W34

The Vertical Clearance sign (W34) shall be used to warn motorists of low structure clearances.

For clearances 15'-6" or less, in addition to the W34B, two advance Vertical Clearance signs shall be installed on the right side of the roadway. The first W34 sign shall be placed in advance of the nearest intersecting street or highway or wide point in the road at which a motorist can detour or safely turn around. A ____ Miles Ahead plate (W34A) should be placed below the W34 sign at this location. The second W34 sign shall be placed in advance of the structure. No W34A plate is needed at the second location.

The W34 sign shall display the same clearance shown on the W34B sign.